

CAMEA LED

Modul



Artikelbezeichnung	Art.Nr.	E-Nummer	Watt	Lumen	Kelvin	Masse mm	CHF / LP
LED Aufbau- Wand- oder Deckenleuchte							
Aufbau Wand- und Deckenleuchte LED 9-12W, 3000 und 4000 Kelvin, Gehäuse Kunststoff weiss, Diffusor PC opal, IP44 / IK10	CAL-O 9 4K	941337109	9	750	4000	Ø300/90	55.10
	CAL-O 12 4K	941337309	12	1100	4000	Ø300/90	60.80
	CAL-O 9 3K	941337209	9	650	3000	Ø300/90	55.10
	CAL-O 12 3K	941337409	12	1000	3000	Ø300/90	60.80
Mit Sensor RCR 360° Aufbau Wand- und Deckenleuchte							
12W, 3000 und 4000 Kelvin, Gehäuse Kunststoff weiss, Diffusor PC opal. IP44 / IK10	CAL-OS 9 4K	941307179	9	750	4000	Ø300/90	82.80
	CAL-OS 12 4K	941307379	12	1100	4000	Ø300/90	88.60
	CAL-OS 9 3K	941307279	9	650	3000	Ø300/90	82.80
	CAL-OS 12 3K	941307479	12	1000	3000	Ø300/90	88.60

